

Fixed radius											
Diameter	R 1	R 2	R 3	R 4	Holding cell, directive	Wall thickness	Fe 235, 355	Aisi 304 EN 1.4301/7	Aisi 316 EN 1.4401	Aisi 441 EN 1.4509	Aluminum
26,9	65				55	2,6-3,6	X				
28,0	70				60	1,5-2,0	X	X	X	X	
30,0	60				50	1,5-3,0	X	X	X		
33,7	80				0	2,6-3,6	X				
38,0	75				70	1,5-2,0	X	X	X	X	
40,0	80				80	1,5	X	X	X		
42,4	85				120	2,0-3,6	X	X	X		
45,5	90				100	10-20	X				
48,3	96				90	2,6	X	X	X		
50,8	70	85	140		90	1,5-2,0	X	X	X	X	
55,0	70				50	1,5-2,0	X				
57,0	85				120	1,5-2,0	X	X	X		
60,3	85	120			115	1,5-2,0	X	X	X		
63,5	85				110	1,5-2,0	X	X	X	X	
70,0	140				150	2,0-2,9	X	X	X		
76,1	76	100	150	(160)	150	1,5-10,0	X	X	X	X	
88,9	89	102	120	170	150	2,0-10,0	X	X	X	X	
90,0	150				150	2,5					X
101,6	101,6	141	170		150	2,0	X	X	X	X	
108,0	170				170	2,0	X	X	X		
114,3	114	190			180	2,0	X	X	X	X	
120,0	200				200	2,0	X				
127,0	127	180	200		170	2,0	X	X	X	X	
139,7	209				200	2,0		X	X		
154,0	231				230	2,0		X	X		

Variable radius, rolling		
Diameter	Minimum radius	Wall thicness
76,1	600	2,0 / 5,0 / 6,3
88,9	750	2,0